Title	The experimental investigation of gas-liquid two phase flow
Sub Title	
Author	佐竹, 祥介(Satake, Shosuke)
Publisher	慶応義塾大学藤原記念工学部
Publication year	1964
Jtitle	Proceedings of the Fujihara Memorial Faculty of Engineering Keio
	University (慶応義塾大学藤原記念工学部研究報告). Vol.17, No.66 (1964.),p.59(15)- 59(15)
JaLC DOI	
Abstract	
Notes	Summaries of Doctor and Master Theses
	Master of Engineering, 1964
	Mechanical Engineering
Genre	Departmental Bulletin Paper
URL	https://koara.lib.keio.ac.jp/xoonips/modules/xoonips/detail.php?koara_id=KO50001004-00170066- 0015

慶應義塾大学学術情報リポジトリ(KOARA)に掲載されているコンテンツの著作権は、それぞれの著作者、学会または出版社/発行者に帰属し、その権利は著作権法によって 保護されています。引用にあたっては、著作権法を遵守してご利用ください。

The copyrights of content available on the KeiO Associated Repository of Academic resources (KOARA) belong to the respective authors, academic societies, or publishers/issuers, and these rights are protected by the Japanese Copyright Act. When quoting the content, please follow the Japanese copyright act.

The Experimental Investigation of Gas-Liquid Two Phase Flow

Shosuke SATAKE*

This report shows the experimental result about gas-liquid two phase flow in vertical and 26° inclined from vertical plane, visible plastics pipes, 25.4 mm in diameter and 2160 mm in length.

Air was used as the gas phase and water as the liquid. The pressure drop and void ratio were measured for 70 cases in mixture ratio. Measured range of flow rate varies 900~2412 kg/hr for water and 1~6 kg/hr for air. A macroscopic analysis of the two phase flow phenomenon in this paper allows the prediction of pressure drop to be calculated as an imaginary single phase flow of gas. Under the assumptions that the velocity distribution of liquid is turbulent, and that the velocity of liquid at the boundary between gas and liquid is V_i , and gas velocity is V_g , the relative velocity of gas and liquid $V_r = V_g - V_i$ at the boundary surface.

The pressure drop may be calculated from the equation,

$$h=\lambda\cdot\frac{L}{d}\cdot\frac{V_r}{2g}$$
 ,

where d is gas phase diameter, and it can be calculated from void ratio. Our results show the nessecity of modificatian, which is proper to individual apparatus, for previous relults obtained by R. C. Martinelli.

*佐竹祥介