Title	Experimental research on the inducer of the cetrifugal compressor
Sub Title	
Author	永野, 徹郎(Nagano, Tetsuro)
Publisher	慶応義塾大学藤原記念工学部
Publication year	1965
Jtitle	Proceedings of the Fujihara Memorial Faculty of Engineering Keio University (慶応義塾大学藤原記念工学部研究報告). Vol.18, No.71 (1965.),p.91(27)- 91(27)
JaLC DOI	
Abstract	
Notes	Summaries of Doctor and Master Theses Master of Engineering, 1965 Mechanical Engineering
Genre	Departmental Bulletin Paper
URL	https://koara.lib.keio.ac.jp/xoonips/modules/xoonips/detail.php?koara_id=KO50001004-00180071- 0027

慶應義塾大学学術情報リポジトリ(KOARA)に掲載されているコンテンツの著作権は、それぞれの著作者、学会または出版社/発行者に帰属し、その権利は著作権法によって 保護されています。引用にあたっては、著作権法を遵守してご利用ください。

The copyrights of content available on the KeiO Associated Repository of Academic resources (KOARA) belong to the respective authors, academic societies, or publishers/issuers, and these rights are protected by the Japanese Copyright Act. When quoting the content, please follow the Japanese copyright act.

Experimental Research on the Inducer of the Cetrifugal Compressor

Tetsuro NAGANO*

Recently the researches for the practical use of the small gasturbines made rapid progress. The small gasturbines are promising as the prime movers of the automobiles. Every element of the construction has an important effect upon the gasturbines. Especially the performance of the compressor gives a large influence upon that of the gasturbine. In experiment, the author used the centrifugal compressor which is used usually in a small gasturbine. Four kinds of inducers were used and the influences which were caused by the difference of the inducer were investigated. In the tests the axial positions and the phase of the inducers were changed, and the results were obtained about adiabatic thermal efficiency, flow rate, pressure ratio, reaction grade, etc.

In consequence, the ordinary type inducer showed the highest efficiency, 0.72, but the operating points exist near to the surging area. On the other hand, the inducer which had a little distance between the inducer and the impeller showed 0.70 efficiency, moreover it showed good flow rate, pressure ratio, and reaction grade. However about the distance between them, there is some limit. The overlap type of the inducer was expected to show a good result, but, on the contrary, its results were completely worse.

*永野徹郎