

Title	A fundamental study on heat transfer of a liquid drop
Sub Title	
Author	信岡, 邦彦(Nonuoka, Kunihiko)
Publisher	慶應義塾大学藤原記念工学部
Publication year	1966
Jtitle	Proceedings of the Fujihara Memorial Faculty of Engineering Keio University (慶應義塾大学藤原記念工学部研究報告). Vol.19, No.76 (1966. ) ,p.232(14)- 232(14)
JaLC DOI	
Abstract	
Notes	Summaries of Doctor and Master Theses Master of Engineering, 1966
Genre	Departmental Bulletin Paper
URL	<a href="https://koara.lib.keio.ac.jp/xoonips/modules/xoonips/detail.php?koara_id=KO50001004-00190076-0014">https://koara.lib.keio.ac.jp/xoonips/modules/xoonips/detail.php?koara_id=KO50001004-00190076-0014</a>

慶應義塾大学学術情報リポジトリ(KOARA)に掲載されているコンテンツの著作権は、それぞれの著作者、学会または出版社/発行者に帰属し、その権利は著作権法によって保護されています。引用にあたっては、著作権法を遵守してご利用ください。

The copyrights of content available on the Keio Associated Repository of Academic resources (KOARA) belong to the respective authors, academic societies, or publishers/issuers, and these rights are protected by the Japanese Copyright Act. When quoting the content, please follow the Japanese copyright act.

# A Fundamental Study on Heat Transfer of a Liquid Drop

Kunihiko NOBUOKA\*

Fundamental data on the rate of heat and mass transfer for a droplet are of importance in the analysis of the operations of spray drying, spray cooling, humidification, combustion, and so on.

The purpose of this paper is to report a fundamental study of evaporation from a water drop. The study was restricted to a low Reynolds number, the range usually encountered in spray drying operation. The Reynolds number was ranged from 80 to 600, drop diameters was ranged from 1.7 to 2.5 mm and air temperatures was ranged from 80 from to 120°C.

A drop was suspended from a glass capillary. The glass was drawn so that small end was 0.3 mm in diameter and the other end was led to a microburet. Evaporation rate for a constant diameter drop was determined by measuring the rate of feed through the buret necessary to maintain a constant diameter. The rate of feed was controlled by water head. The liquid was warmed up to the temperature of the drop and was fed to the drop.

Equation for correlation of our experimental data was obtained as follows :

$$\text{Nu} = 2 + 0.196 \text{Re}^{0.7}$$

when  $80 < \text{Re} < 600$  and  $\text{Pr}=0.69$ .

---

\*信 岡 邦 彦