

Title	The plastic collapse of aluminium ring
Sub Title	
Author	前田, 昭彦(Meda, Akihiko)
Publisher	慶応義塾大学藤原記念工学部
Publication year	1967
Jtitle	Proceedings of the Fujihara Memorial Faculty of Engineering Keio University (慶応義塾大学藤原記念工学部研究報告). Vol.20, No.81 (1967. ) ,p.191(15)- 191(15)
JaLC DOI	
Abstract	
Notes	Summaries of Doctor and Master Theses
Genre	Departmental Bulletin Paper
URL	<a href="https://koara.lib.keio.ac.jp/xoonips/modules/xoonips/detail.php?koara_id=KO50001004-00200081-0015">https://koara.lib.keio.ac.jp/xoonips/modules/xoonips/detail.php?koara_id=KO50001004-00200081-0015</a>

慶應義塾大学学術情報リポジトリ(KOARA)に掲載されているコンテンツの著作権は、それぞれの著作者、学会または出版社/発行者に帰属し、その権利は著作権法によって保護されています。引用にあたっては、著作権法を遵守してご利用ください。

The copyrights of content available on the KeiO Associated Repository of Academic resources (KOARA) belong to the respective authors, academic societies, or publishers/issuers, and these rights are protected by the Japanese Copyright Act. When quoting the content, please follow the Japanese copyright act.

## The Plastic Collapse of Aluminium Rings

Akihiko MAEDA\*

The problems of column buckling, and the concepts to be used in the design of slender metal columns, have been a constant concern of structural engineers. In order to clarify these problems, the behaviour of ring specimens having rectangular cross section, in compression and bending, was analyzed.

The direct measurement of buckling loads of columns has been popular so far, but in this method, the conditions of end-fitting might be remarkably influential. Therefore, unless ideal conditions of end-fitting are performed, a number of problems might arise in actual analysis.

In this paper, the experiment was performed as follows: The collapse loads  $P_c$  were plotted in the ordinate and the ratios  $t^2/R_m$  of the second power of thickness to mean radii  $R_m$  in the abscisa.

By comparing the expression obtained by this experiment, with the expression connecting the yield stress with the collapse load in plastic design, the yield stress  $\sigma_r$ , in compression and bending, was obtained. The results were as follows.

The value of the stress was constant and 2% lower than that of standard yield strength.

The relation between  $P_c$  and  $t^2/R_m$  was found to be a linear one,

$$P_c = K \cdot (t^2/R_m).$$

It was seen that the strength of members in compression and bending can be calculated by this method.

---

\*前 田 昭 彦