Title	On vibration of two circular cylinders which are immersed in a water region-II
Sub Title	
Author	鬼頭, 史城(Kito, Fumiki)
Publisher	慶応義塾大学工学部
Publication year	1979
Jtitle	Keio engineering reports Vol.32, No.5 (1979. 4) ,p.45- 56
JaLC DOI	
Abstract	In former report, under the same title, which appeared about ten years ago, by the same author, we made an analytical study with regard to vibration of two circular cylinders which are immersed in a fluid region of infinite extent. Therein, the vibration was assumed to be of infinitesimally small magnitude. The present paper is the continuation of analytical study of the same problem, and here we treat the case of vibration of finite amplitudes. As before, we take the case of two dimensional problem about an ideal fluid. In the present study, (Part II), only main analytical formulae about this problem is given, more detailed account together with numerical example being to be given in subsequent paper.
Notes	
Genre	Departmental Bulletin Paper
URL	https://koara.lib.keio.ac.jp/xoonips/modules/xoonips/detail.php?koara_id=KO50001004-00320005- 0045

慶應義塾大学学術情報リポジトリ(KOARA)に掲載されているコンテンツの著作権は、それぞれの著作者、学会または出版社/発行者に帰属し、その権利は著作権法によって 保護されています。引用にあたっては、著作権法を遵守してご利用ください。

The copyrights of content available on the KeiO Associated Repository of Academic resources (KOARA) belong to the respective authors, academic societies, or publishers/issuers, and these rights are protected by the Japanese Copyright Act. When quoting the content, please follow the Japanese copyright act.

# ON VIBRATION OF TWO CIRCULAR CYLINDERS WHICH ARE IMMERSED IN A WATER REGION—II.

**FUMIKI KITO\*** 

## Dept. of Mechanical Engineering, Keio University, Hiyoshi, Yokohama 223, Japan

(Received April, 19 1979)

## ABSTRACT

In former report, under the same title, which appeared about ten years ago, by the same author, we made an analytical study with regard to vibration of two circular cylinders which are immersed in a fluid region of infinite extent. Therein, the vibration was assumed to be of infinitesimally small magnitude. The present paper is the continuation of analytical study of the same problem, and here we treat the case of vibration of finite amplitudes. As before, we take the case of two dimensional problem about an ideal fluid. In the present study, (Part II), only main analytical formulae about this problem is given, more detailed account together with numerical example being to be given in subsequent paper.

## 1. Statement of the Problem.

In Fig. 1, two circular cylinders are shown, which represents the initial configuration, at time t=0. Radii of two circular cylinders are  $R_1$  and  $R_2$ . They are immersed in water region of infinite extent, which is considered to be an ideal fluid. Positions of centers of two circular cylinders are located on the x-axis, and are spaced by a distance  $D=E_0$  each other. Radii  $R_1$  and  $R_2$  are to be kept constant at every subsequent time t ( $0 \le t$ ).

Positions of centers of two circular cylinders are considered to move afterwards (at  $0 \le t$ ), in a prescribed manner. Fig. 2 shows us positions of two circular cylinders at time t. The two cylinders have moved by distances  $a_1$  and  $a_2$ , in angular directions  $\beta_1$  and  $\beta_2$  respectively. In what follows, we take up the case in which  $a_1$  and  $a_2$  are given functions of time t, while angles  $\beta_1$  and  $\beta_2$  are kept

<sup>\*</sup> Professor Emeritus of Keio University.





Fig. 1. Position of two Circular Cylinders at initial State. (t=0)



Fig. 2. Position of two Circular Cylinders at displaced State (at time t)

at constant values. Displacements of centers  $a_1$  and  $a_2$  need not to be taken as of small amount.

Our problem of the present paper is to make an analytical study about the fluid motion set up, and also about the resulting hydrodynamic forces set up on walls of two cylinders. The surrounding fluid being assumed to be an ideal fluid of infinite extent, we are to treat the problem as a case of two-dimensional potential flow (which necessarily contain time t as another independent variable.)

On Vibration of two Ciucular Cylinders which are immersed in a Water Region-II.

In the present report, only general expressions corresponding to our aim is given, more detailed account being left for a future report.

# 2. Notations used.

 $x, y = \operatorname{rectangular}$  coordinates of a point in xy plane z = x + iy a complex variable  $c = \operatorname{distance}$  from origin 0, of radical centers of system of bipolar coordinates  $h = \operatorname{coefficient}$  of linear element for the case of bipolar coordinates  $(\xi, \eta)$   $\xi, \eta = a$  system of bipolar coordinates representing any point on xy plane  $R_i = \operatorname{radius}$  of circular cylinder (i=1, 2)  $E_i = \operatorname{position}$  of center of ditto  $p = \operatorname{fluid}$  pressure,  $\rho = \operatorname{density}$  of the fluid  $\phi = \operatorname{velocity}$  potential of fluid motion, giving absolute velocity of flow

In what follows, several coefficients  $A_i$ ,  $B_i$ ,  $C_i$  etc., will be used for giving us the solution in form of an infinite series. These coefficients will be defined where they make first appearances. These coefficients are independent of variables x, y(also  $\xi, \eta$ ), but they may be functions of time t, because we are treating the case of non-stationary fluid motion. Also, suffixes will be attached to them for distinguishing individual cases of application.

# 3. Fundamental Formulae.

The main formula used in the present paper will be (as in previous report, Ref. (1)) those relating to a system of bipolar coordinates, and is given below.



Fig. 3. Configuration of two circular Cylinders, represented by bipolar Coordinates

## **Fumiki Kito**

Referring to Fig. 3, two points (+c, 0) and (-c, 0) lying on the real axis are taken as radical centers, and we define a system of bipolar coordinates  $(\xi, \eta)$  by means of the relation

$$\xi + i\eta = \log \frac{c+z}{c-z} \tag{1}$$

wherein we have z=x+iy.

From this eq. (1), we obtain

$$x = \frac{c \, \mathrm{sh}\,\xi}{\mathrm{ch}\,\xi + \cos\eta}, \, y = \frac{c \, \sin\eta}{\mathrm{ch}\,\xi + \cos\eta} \tag{2}$$

The linear element ds is given by

$$(ds)^{2} = (dx)^{2} + (dy)^{2} = h^{2}[(d\xi)^{2} + (d\eta)^{2}]$$
(3)

in which we have put

$$h = \frac{\operatorname{ch} \xi + \cos \eta}{c} \tag{4}$$

Therefore, two-dimensional Laplacian  $\Delta \phi$  of the function  $\phi$  is given by

$$\varDelta \phi \equiv \frac{\partial^2 \phi}{\partial x^2} + \frac{\partial^2 \phi}{\partial y^2} \equiv \frac{1}{h^2} \left( \frac{\partial^2 \phi}{\partial \xi^2} + \frac{\partial^2 \phi}{\partial \eta^2} \right)$$

For the case of an ideal fluid, we have to put  $\Delta \phi = 0$ , whose general solution may be given in following form,

$$\phi = \sum_{n=1}^{\infty} [A_n \sin n\eta + B_n \cos n\eta] \cdot [\sinh n\xi + C_n \cosh n\xi]$$
(5)

 $A_n$  and  $B_n$ ,  $C_n$  are constants independent of variables  $\xi$ ,  $\eta$ . But in our case of non-steady fluid motion, they may be functions of time t.

In order to apply these fundamental formula to our problem, we take two circular cylinders to be represented by  $\xi = \xi_1$  and  $\xi = \xi_2$  respectively.  $\xi_1$  is positive, but  $\xi_2$  has a negative value.

For a given set  $(\xi_1, \xi_2)$  of values for two circles, we have (k=1, 2)

$$E_{k} = c \frac{\operatorname{ch} \xi_{k}}{\operatorname{sh} \xi_{k}}, \quad R_{k} = c \frac{1}{|\operatorname{sh} \xi_{k}|} \tag{6}$$

Corresponding to the instantaneous state of flow given by eq. (5), value of absolute velocity of flow normal to wall surfaces of circular cylinders are given by

$$V_{n} = -\frac{\partial \phi}{h\partial \xi}$$
$$= (-)^{k+1} \frac{1}{c} (\operatorname{ch} \xi_{k} + \cos \eta) \times$$

On Vibration of two Circular Cylinders which are immersed in a Water Region--II.

$$\times \sum_{n} n(A_n \sin n\eta + B_n \cos n\eta) \cdot (\operatorname{ch} n\xi_k + C_n \operatorname{sh} n\xi_k)$$
(7)

at  $\xi = \xi_k$  (k=1, 2). The sense of  $V_n$  is taken as positive in outward direction with regard to each one of cylinder wall. Also, we note that  $\xi_1$  is positive, while  $\xi_2$ is negative. If values of  $V_n$  along two circumferences  $\xi = \xi_1$  and  $\xi = \xi_2$  (as functions of  $\eta$ ) are given by hydrodynamic consideration, we can obtain values of coefficients  $A_i$ ,  $B_i$  and  $C_i$  from the eq. (7), by means of so-called Fourier analysis.

# 4. Value of Velocity Potential for Instantaneous State of Fluid Motion.

In order to apply the fundamental formula as given above to obtain value of velocity potential  $\phi$  which gives us instantaneous state of fluid motion at time t, we take  $\phi$  in such way that it represents the state of matters as shown in Fig. 2. Thus, in order to conform the state of Fig. 3 to instantaneous configuration of Fig. 2, we take the line  $P_1P_2$  of Fig. 2 to correspond to x-axis of Fig. 3. Also, we take

$$[|E_1| + |E_2|]^2 = E_0^2$$
  
=  $(D + a_1 \cos \beta_1 - a_2 \cos \beta_2)^2 + (a_1 \sin \beta_1 - a_2 \sin \beta_2)^2$  (8)

Moreover, we have

$$E_{0} = |E_{1}| + |E_{2}| = R_{1} \operatorname{ch} \xi_{1} + R_{2} \operatorname{ch} \xi_{2}$$

$$c = \frac{1}{2E_{0}} [\{E_{0}^{2} - (R_{1} - R_{2})^{2}\}\{E_{0}^{2} - (R_{1} + R_{2})^{2}\}]^{1/2}$$

$$\xi_{1} = \log \frac{c + \sqrt{c^{2} + R_{1}^{2}}}{R_{1}}$$

$$|\xi_{2}| = \log \frac{c + \sqrt{c^{2} + R_{2}^{2}}}{R_{2}}$$

$$(9)$$

Angle  $\mu$  of inclination of new x-axis  $P_1P_2$  to old x-axis is given by

$$\tan \mu = \frac{a_1 \sin \beta_1 - a_2 \sin \beta_2}{D + a_1 \cos \beta_1 - a_2 \cos \beta_2}$$
(10)

When two cylinders are moving with velocities  $\dot{a}_k$  (k=1, 2) in directions of  $\beta_k$  respectively (relative to old axis), normal velocities (taken outwardly) of their wall surfaces are given by (k=1, 2)

$$V_{\nu} = \frac{d}{dt} (a_k) \cos(\nu, \gamma_k) = \dot{a}_k \cos(\theta - \gamma_k)$$
(11)

in which we have

$$\cos\theta = (x - E_k)/R_k, \sin\theta = y/R_k$$

$$x = \frac{c \, \mathrm{sh}\,\xi_k}{\mathrm{ch}\,\xi_k + \cos\eta}, \quad y = \frac{c \, \sin\eta}{\mathrm{ch}\,\xi_k + \cos\eta}$$
(12)

It is to be noted that directions of motion  $\gamma_1$  and  $\gamma_2$  (with respect to new instantaneous *x*-axis) are related to original directions of motion  $\beta_1$  and  $\beta_2$  by the equation

$$\gamma_k = \beta_k - \mu \ (k = 1, 2) \tag{13}$$

When two circular cylinders are moving through the fluid in a prescribed manner, we must have  $V_n = V_{\nu}$  on both wall surfaces  $\xi = \xi_k$  (k=1,2) of two cylinders. Thus, we could evaluate coefficients  $A_n, B_n, C_n$   $(n=1, 2, \cdots)$  of eq. (5) by means of Fourier analysis, as mentioned above. We find it more convenient to take

$$\phi = \phi_1 + \phi_2 \tag{14}$$

where  $\phi_1$  satisfies the boundary condition at wall of No. 1 cylinder  $(\xi = \xi_1)$  while the No. 2 cylinder remain at rest. On the other hand,  $\phi_2$  satisfies the boundary condition at wall of No. 2 cylinder  $(\xi = \xi_2)$  while the No. 1 cylinder is kept at stand-still. It is to be noted that the solution (14) gives us an instantaneous value of velocity potential  $\phi$ , pertaining to the motion of an ideal fluid. Actual values of these coefficients obtained by this means are as given below. Thus, we put

$$\phi_k = \sum_n \left( A_{nk} \sin n\eta + B_{nk} \cos n\eta \right) \cdot (\sinh n\xi + C_{nk} \cosh n\xi)$$
(15)

where we have (for k=1, 2)

$$A_{nk} = -\frac{H_k}{nD_{nk}} [K_{n-1}^{(2)}(\lambda_k) - K_{n+2}^{(2)}(\lambda_k)]$$

$$B_{nk} = -\frac{G_k}{nD_{nk}} [2K_n^{(2)}(\lambda_k)]$$

$$+ \frac{2c\dot{a}_k \cos\gamma_k \operatorname{ch} \xi_k}{nD_{nk}} [K_n^{(1)}(\lambda_k)]$$

$$H_k = \frac{\dot{a}_k c^2}{R_k} \sin\gamma_k$$

$$G_k = \frac{\dot{a}_k c^2}{R_k} \operatorname{sh} \xi_k \cos\gamma_k$$

On Vibration of two Circular Cylinders which are immersed in a Water Region-II.

$$D_{n1} = \frac{\operatorname{sh} n(\xi_2 - \xi_1)}{\operatorname{sh} n\xi_2}$$
$$D_{n2} = \frac{\operatorname{sh} n(\xi_1 - \xi_2)}{\operatorname{sh} n\xi_1}$$

It is to be noted that  $\xi_1$  is positive, while  $\xi_2$  is negative. In the above formula, following values of definite integrals were used, these being used already in author's previous report.

$$\begin{split} K_m^{(1)}(\lambda) &= \frac{1}{2\pi} \int_0^{2\pi} \frac{\cos m\eta}{(\lambda + \cos \eta)} \, d\eta \\ &= (-)^m \frac{2\varepsilon^{m+1}}{(1 - \varepsilon^2)} \\ K_m^{(2)}(\lambda) &= \frac{1}{2\pi} \int_0^{2\pi} \frac{\cos m\eta}{(\lambda + \cos \eta)^2} \, d\eta \\ &= (-)^m \frac{4(m+1)\varepsilon^{m+2}}{(1 - \varepsilon^2)^2} + (-)^m \frac{8\varepsilon^{m+4}}{(1 - \varepsilon^2)^3} \end{split}$$

wherein we write for shortness

$$\varepsilon = \frac{1}{\lambda + \sqrt{\lambda^2 - 1}} = \frac{1}{\operatorname{ch} \xi + |\operatorname{sh} \xi|} < 1$$
$$\lambda = \operatorname{ch} \xi$$

m is positive integers,  $0, 1, 2, \cdots$ 

Especially, for the values of  $\phi_s$  (s=1, 2) at two cylindrical walls (at which  $\xi = \xi_p$ ; p = 1, 2) we have

$$\phi_s^{(p)} = \sum_n \left[ A_{ns}^{(p)} \sin n\eta + B_{ns}^{(p)} \cos n\eta \right]$$
(16)

Actual values of coefficients  $A_{ns}^{(p)}$  and  $B_{ns}^{(p)}$  are as follows;

$$\begin{aligned} A_{n1}^{(1)} &= \frac{-1}{n} \left[ \frac{c^2 \dot{a}_1}{R_1} \sin \gamma_1 \right] \coth n(\xi_1 - \xi_2) \cdot \left[ K_{n-1}^{(2)}(\lambda_1) - K_{n+1}^{(2)}(\lambda_1) \right] \\ B_{n1}^{(1)} &= \frac{-2}{n} \left[ c \dot{a}_1 \cos \gamma_1 \right] \coth n(\xi_1 - \xi_2) \cdot \left[ \operatorname{sh}^2 \xi_1 K_n^{(2)}(\lambda_1) - \operatorname{ch} \xi_1 K_n^{(1)}(\lambda_1) \right] \\ A_{n1}^{(2)} &= \frac{-1}{n} \left[ \frac{c^2 \dot{a}_1}{R_1} \sin \gamma_1 \right] \frac{1}{\operatorname{sh} n(\xi_1 - \xi_2)} \cdot \left[ K_{n-1}^{(2)}(\lambda_1) - K_{n+1}^{(2)}(\lambda_1) \right] \\ B_{n1}^{(2)} &= \frac{-2}{n} \left[ c \dot{a}_1 \cos \gamma_1 \right] \frac{1}{\operatorname{sh} n(\xi_1 - \xi_2)} \cdot \left[ \operatorname{sh}^2 \xi_1 K_n^{(2)}(\lambda_1) - \operatorname{ch} \xi_1 K_n^{(1)}(\lambda_1) \right] \\ A_{n2}^{(1)} &= \frac{-1}{n} \left[ \frac{c^2 \dot{a}_2}{R_2} \sin \gamma_2 \right] \frac{1}{\operatorname{sh} n(\xi_1 - \xi_2)} \cdot \left[ K_{n-1}^{(2)}(\lambda_2) - K_{n+1}^{(2)}(\lambda_2) \right] \end{aligned}$$

$$B_{n2}^{(1)} = \frac{-2}{n} [c\dot{a}_{2}\cos\gamma_{2}] \frac{1}{\sinh n(\xi_{1} - \xi_{2})} \cdot [-(\sinh \xi_{2})^{2} K_{n}^{(2)}(\lambda_{2}) + \cosh \xi_{2} K_{n}^{(1)}(\lambda_{2})] \cdot A_{n2}^{(2)} = \frac{-1}{n} \left[ \frac{c^{2}\dot{a}_{2}}{R_{2}}\sin\gamma_{2} \right] \coth n(\xi_{1} - \xi_{2}) \cdot [K_{n-1}^{(2)}(\lambda_{2}) - K_{n+1}^{(2)}(\lambda_{2})] \\B_{n2}^{(2)} = \frac{-2}{n} [c\dot{a}_{2}\cos\gamma_{2}] \coth n(\xi_{1} - \xi_{2}) \cdot [-(\sinh \xi_{2})^{2} K_{n}^{(2)}(\lambda_{2}) + \cosh \xi_{2} K_{n}^{(1)}(\lambda_{2})]$$

It will be observed that infinite series solutions (15) and (16) are absolutely convergent. After numerical estimation about some practical cases, we find that the convergence is fairly good, and we may stop at n=1, 2, ... to ..., 5.

#### 5. Hydrodynamical Forces acting on each Circular Cylinders

As mentioned above, we take as instantaneous location of x-axis, the straight line  $P_1P_2$  of Fig. 2. When the time t elapses, the location of line  $P_1P_2$  changes. Therefore, in order to evaluate fluid pressure p, we must have recourse to theory of hydrodynamics for the case of moving axes of reference. This has been done by the present author and is described in previous paper (Ref. (2)). In our case of two dimensional flow, it can be given in following form;

$$-\frac{1}{\rho}p + U = \frac{\partial\phi}{\partial t} + \frac{1}{2} \left\{ \left( \frac{\partial\phi}{\partial x} \right)^2 + \left( \frac{\partial\phi}{\partial y} \right)^2 \right\} \\ - (c_x - \Omega y) \frac{\partial\phi}{\partial x} - (c_y + \Omega x) \frac{\partial\phi}{\partial y} + C$$
(17)

In this eq. (17), U is the potential of external force field, which we take here  $U \equiv 0$ . C is an arbitrary constant independent of x, y but it may be a function of time t. Here also, we take  $C \equiv 0$ .  $(c_x, c_y)$  is linear velocity of motion of the origin of our instantaneous frame of axes,  $\Omega$  being its angular velocity of rotation about an axis perpendicular to x, y plane.

Taking the velocity potential  $\phi$  to be given by eqs. (14), (15), and putting it into eq. (17), we can estimate the amount of hydrodynamic forces exerted by the fluid pressure p, upon two wall surfaces of circular cylinders, thus;

(1) Hydrodynamical Force acting upon Wall of No. 1 Circular Cylinder.

$$F_{x} = \int_{0}^{2\pi} \left[-p\right] \left[ \left(\frac{c}{R_{1}}\right)^{2} \frac{1}{\operatorname{ch}\xi_{1} + \cos\eta} - \operatorname{ch}\xi_{1} \right] \cdot \left[\frac{c}{\operatorname{ch}\xi_{1} + \cos\eta}\right] d\eta$$
(18)

$$F_{y} = \int_{0}^{2\pi} [-p] \left[ \frac{c^{2}}{R_{1}} \frac{\sin \eta}{(\cosh \xi_{1} + \cos \eta)^{2}} \right] d\eta$$
(19)

(2) Hydrodynamic Force acting upon Wall of No. 2 Circular Cylinder.

$$F_x = \int_0^{2\pi} [+p] \left[ \left( \frac{c}{R_2} \right)^2 \frac{1}{\operatorname{ch} \xi_2 + \cos \eta} - \operatorname{ch} \xi_2 \right] \cdot \left[ \frac{c}{\operatorname{ch} \xi_2 + \cos \eta} \right] d\eta \tag{20}$$

On Vibration of two Circular Cylinders which are immersed in a Water Region-II.

$$F_{y} = \int_{0}^{2\pi} [-p] \left[ \frac{c^{2}}{R_{2}} \frac{\sin \eta}{(\cosh \xi_{2} + \cos \eta)^{2}} \right] d\eta$$
(21)

In what follows, we shall show actual expressions of hydrodynamic forces  $F_x$ ,  $F_y$  for the case in which  $a_1 \neq 0$ ,  $a_2 \equiv 0$ , this being done for presenting simpler expressions. Task of evaluation of  $F_x$ ,  $F_y$  may be done, conveniently, in following four steps.

(A) Effect of the Term  $\partial \phi / \partial t$ 

As we see from eq. (17), we must first evaluate the effect of term  $\partial \phi / \partial t$  upon  $F_x$  and  $F_y$ . This is done, for No. 1 cylinder, by evaluating following definite integrals:

$$F_x = -\rho \int_0^{2\pi} \frac{\partial \phi}{\partial t} \left[ \frac{c}{R_1} \frac{\operatorname{sh} \xi_1}{\operatorname{ch} \xi_1 + \cos \eta} - \frac{E_1}{R_1} \right] \cdot \left[ \frac{c}{\operatorname{ch} \xi_1 + \cos \eta} \right] d\eta \tag{22}$$

$$F_{y} = -\rho \int_{0}^{2\pi} \frac{\partial \phi}{\partial t} \left[ \frac{c^{2}}{R_{1}} \frac{\sin \eta}{\cosh \xi_{1} + \cos \eta} \right] d\eta$$
(23)

Value of velocity potential  $\phi$ , contained in these definite integrals, being the value at  $\xi = \xi_1$ , we take it in form of eq. (16), in which we have s=1, p=1. Moreover, differentiation  $\partial/\partial t$ , with respect to time t, must be carried out in two ways. The first one is with regard to  $\dot{a}_1$ , and write

$$\frac{d}{dt}(\dot{a}_1) = \ddot{a}_1$$

The second is with respect to  $a_1$ , which is contained implicitly in coefficients  $A_{ns}^{(p)}$  and  $B_{ns}^{(p)}$  (through c,  $E_1$ , etc.) and this term may conveniently be expressed formally as

$$\frac{\partial \phi}{\partial a_1} \frac{\partial a_1}{\partial t} = \frac{\partial \phi}{\partial a_1} \dot{a}_1$$

We may express this fact by writing

$$\frac{d\phi}{dt} = \frac{\partial\phi}{\partial\dot{a}_1}\ddot{a}_1 + \frac{\partial\phi}{\partial a_1}\dot{a}_1$$

The author finds it more convenient to put

$$A_{n_1}^{(1)} = [D\dot{a}_1]a_{n_1}^{(1)}$$
$$B_{n_1}^{(1)} = [D\dot{a}_1]b_{n_1}^{(1)}$$

etc., where  $a_{n1}^{(1)}, b_{n1}^{(1)}$  are numerical (non-dimensional) coefficients, which depend implicitly on  $a_1$ .

Furthermore, we have

$$\frac{\partial}{\partial t} [a_{n1}^{(1)}] = \frac{\partial}{\partial a_1} [a_{n1}^{(1)}] \dot{a}_1 = \alpha_{n1}^{(1)} \dot{a}_1$$
$$\frac{\partial}{\partial t} [b_{n1}^{(1)}] = \frac{\partial}{\partial a_1} [b_{n1}^{(1)}] \dot{a}_1 = \beta_{n1}^{(1)} \dot{a}_1$$

Strictly speaking, values of coefficients  $\alpha_{n_1}^{(1)}$ ,  $\beta_{n_1}^{(1)}$ , etc., are to be obtained by actuating process of differentiation, which is very complicated. However, the author has found a practical method of estimating them approximately, which will be reported subsequently. Under these preparatory notices, we obtain

$$F_x = \sum_n \rho n \pi \left(\frac{c}{D}\right) \left(\frac{D}{R_1}\right) \left(\frac{D}{\cos \gamma_1}\right) \cdot \frac{\tanh n(\xi_1 - \xi_2)}{\sinh \xi_1} \cdot [b_{n_1}^{(1)}] \left[\frac{dB_{n_1}^{(1)}}{dt}\right]$$
(24)

$$F_{y} = \sum_{n} \frac{\rho n \pi D}{\sin \gamma_{1}} \tanh n(\xi_{1} - \xi_{2}) \cdot [a_{n1}^{(1)}] \left[ \frac{d A_{n1}^{(1)}}{dt} \right]$$
(25)

Therein, we have

$$\frac{dB_{n1}^{(1)}}{dt} = D\ddot{a}_1 b_{n1}^{(1)} + D \frac{\partial b_{n1}^{(1)}}{\partial a_1} (\dot{a}_1)^2$$
$$\frac{dA_{n1}^{(1)}}{dt} = D\ddot{a}_1 a_{n1}^{(1)} + D \frac{\partial a_{n1}^{(1)}}{\partial a_1} (\dot{a}_1)^2$$

Summing up these results, we see that hydrodynamic forces  $F_x$ ,  $F_y$  may be expressed in following form;

$$F_{x} = K_{x} \ddot{a}_{1} + S_{x} (\dot{a}_{1})^{2}$$

$$F_{y} = K_{y} \ddot{a}_{1} + S_{y} (\dot{a}_{1})^{2}$$

$$(26)$$

We observe that, coefficients  $K_x, K_y$  of acceleration term  $\ddot{a}_1$  just coincide with those obtained (in Report I) for the case of small vibration. Terms  $S_x(\dot{a}_1)^2, S_y(\dot{a}_1)^2$  are newly added terms representing non-linearity for the case of finite vibrations.

(B) Contribution by the term  $[(\partial \phi/\partial x)^2 + (\partial \phi/\partial y)^2]$ . Here we have

$$\left(\frac{\partial\phi}{\partial x}\right)^2 + \left(\frac{\partial\phi}{\partial y}\right)^2 = \frac{1}{h^2} \left[ \left(\frac{\partial\phi}{\partial \xi}\right)^2 + \left(\frac{\partial\phi}{\partial \eta}\right)^2 \right]$$

Also, we have, on the wall surface

$$-\frac{1}{h}\frac{\partial\phi}{\partial\xi}=V_{\nu}$$

and total effect of the term  $(1/h^2) [(\partial \phi/\partial \xi)]^2$  on  $F_x, F_y$  is null, due to consideration of symmetry. So that we need only to put

$$\frac{1}{2} \rho \frac{1}{h^2} \left[ \left( \frac{\partial \phi}{\partial \eta} \right)^2 \right]$$

into formulae (18) and (19), instead of p there; We thus obtain the following values;

$$F_{x} = -\frac{\rho}{2c} \int_{0}^{2\pi} \left[ \sum_{n} \{ nA_{n} \cos n\eta - nB_{n} \sin n\eta \} \cdot \{ \operatorname{sh} n\xi_{k} + C_{n} \operatorname{ch} n\xi_{k} \} \right]^{2} \\ \cdot \left[ \frac{c}{R_{k}} \operatorname{sh} \xi_{k} - \frac{E_{k}}{R_{k}} \left( \operatorname{ch} \xi_{k} + \cos \eta \right) \right] d\eta$$

$$(27)$$

On Vibration of two Circular Cylinders which are immersed in a Water Region-II.

$$F_y = -\frac{\rho}{2} \int_0^{2\pi} \left[ \sum_n \left\{ nA_n \cos n\eta - nB_n \sin n\eta \right\} \cdot \left\{ \sin n\xi_k + C_n \cosh n\xi_k \right\} \right]^2 \frac{\sin \eta}{R_k} \, d\eta \tag{28}$$

Actual values of  $F_x$ ,  $F_y$  can be obtained in form of infinite series, consisting of each term in form of squares and products of  $A_{n1}^{(1)}$  and  $B_{n1}^{(1)}$ . We observe that these component parts of forces  $F_x$ ,  $F_y$  are proportional to  $(\dot{a}_1)^2$ .

(C) Effect of Term which contains the Factor  $\Omega$  in eq. (17)

In this case we have to put

$$\rho \Omega \left[ y \frac{\partial \phi}{\partial x} - x \frac{\partial \phi}{\partial y} \right]$$

in place of p in eqs. (18), (19). But we have, by definition of eq. (1),

$$\frac{\partial \xi}{\partial x} = \frac{2c[c^2 - (x^2 - y^2)]}{S}$$
$$\frac{\partial \xi}{\partial y} = -\frac{4cxy}{S}$$
$$\frac{\partial \eta}{\partial x} = \frac{4cxy}{S}$$
$$\frac{\partial \eta}{\partial y} = \frac{2c[c^2 - (x^2 - y^2)]}{S}$$

where we put, for shortness

$$S \!=\! [c^2 \!-\! (x^2 \!-\! y^2)]^2 \!+\! [2xy]^2$$

So that we have, by inter-change of independent variables from (x, y) to  $(\xi, \eta)$ ;

$$y\frac{\partial\phi}{\partial x} - x\frac{\partial\phi}{\partial y} = \frac{\partial\phi}{\partial\xi}\operatorname{ch}\xi\sin\eta - \frac{\partial\phi}{\partial\eta}\operatorname{sh}\xi\cos\eta$$
(29)

Thus, we have to replace p in eqs. (20) and (21) by the expression

$$\rho \Omega \left[ \frac{\partial \phi}{\partial \xi} \operatorname{ch} \xi_k \sin \eta - \frac{\partial \phi}{\partial \eta} \operatorname{sh} \xi_k \cos \eta \right]$$

The result will be given in a form of infinite series about factors  $A_{n1}^{(1)}, B_{n1}^{(1)}$ . Moreover, if we confine our-selves to the case in which  $\dot{a}_1 \neq 0$ ,  $a_2 \equiv 0$ , we readily see that the angular velocity  $\Omega$  of rotation of moving axes is proportional to  $\dot{a}_1$ . Thus finally, we infer that we may write

$$F_x = Q_x(\dot{a}_1)^2, F_y = Q_y(\dot{a}_1)^2$$

where factors  $Q_x, Q_y$  are easily determined by infinite series (14), (15) for velocity potential  $\phi$ .

(D) Effect of Term containing  $c_x$  and  $c_y$ .

Her we have, also by interchange of independent variables from (x, y) to  $(\xi, \eta)$ ,

$$\rho \left[ c_x \frac{\partial \phi}{\partial x} + c_y \frac{\partial \phi}{\partial y} \right]$$
  
=  $\rho \frac{\partial \phi}{\partial \xi} \left[ \frac{c_x}{c} (1 + \operatorname{ch} \xi \cos \eta) - \frac{c_y}{c} \operatorname{sh} \xi \sin \eta \right]$   
+  $\rho \frac{\partial \phi}{\partial \eta} \left[ \frac{c_x}{c} \operatorname{sh} \xi \sin \eta - \frac{c_y}{c} (1 + \operatorname{ch} \xi \cos \eta) \right]$  (30)

So that we replace p in eqs. (18), (19) by this amount (30) (where we put  $\xi = \xi_k$ ). Thus, the same inference as we made for above item (C) can also be made about the present item (D).

## 6. Concluding Remark.

Thus far, the author has reported results of his analytical study about vibration of two circular cylinders which are immersed in a region of ideal fluid, which extend to infinity. The magnitude of displacements  $a_1$  and  $a_2$  are taken to be of finite amounts (not necessarily of small amounts), this leading us to nonlinear theory. In the above presentation, only main line of analysis is given. The author has made more detailed treatment, together with some examination of numerical values. It is hoped that these matters will be reported in subsequent papers.

#### REFERENCES

- KITO, F. (1967): On Vibration of two Circular Cylinders which are immersed in Water Region, Keio Engineering Reports, 20, No. 77, pp. 27-38.
- [2] KITO, F. (1977): On Motion of an Ideal Fluid which is filled up in a Rotating Vessel, Keio Engineering Reports, 30, No. 1, pp. 1-12.
- [3] KITO, F. (1977): Ditto, -II, Keio Engineering Reports, 30, No. 11, pp. 131-146.
- [4] P. CAPODANNO (1967): Sur le Calul des Efforts Aerodynamiques exerces par un Fluide parfait irrotationnel, au Repos a l'infini, sur un Couple de Profils anime d'un Mouvement quelconque, Jour. de Mathematiques pures et appliquees, 46, pp. 249-278.

[CORRECTION to Fig. 2:  $r_1 \rightarrow \beta_1$ ;  $r_2 \rightarrow \beta_2$ ]